

Key **Features**

- Shared HDMI/MHL display interface
- Easy Streaming from 3rd Party Apps
- Enterprise WiFi Routers
- Cleverly Concealed Wireless
 Projection
- Unobstructed Viewing from Any Seat



Product **Description**

VC10 is a powerful and compact wireless dongle that enables content to be streamed wirelessly from mobile devices, PCs, and laptops to any projector or display. With its shared HDMI/MHL interface, VC10 is designed for cable-free connection and setup, making your wireless presentations easy and effective in any meeting room or classroom. The VC10 wireless dongle supports commonly used WiFi display standards which allows users to stream content to any display, while enterprise WiFi router access allows users to access business networks. In addition, VC10 can be plugged directly into ViewSonic's PortAll® dongle compartment to provide wireless projection with ViewSonic projectors.

Visit Us — www.viewsonic.com

16/03/2019 datasheet_VC10

KEY COMPONENT	
Processor:	Action Micro AM8251
Wireless Module:	RTL8192EU 2.4G 2T/2R
SYSTEM REQUIREMET	
	• w/o smoothly video playback : Celeron

STSTEIN REQUIRENIET	
WiFi Display(vPresenter Pro):	 w/o smoothly video playback: Celeron 2.0G above CPU Video playback smoothly – i5 2.4G CPU with SandyBridge iOS 7 and above Android 4.0 and above

WIRELESS NETWORK

	Built-in 802.11 b/g/n
Interface:	2T2R
Frequency Band:	2.4GHz(2.312~2.472GHz) 2.484GHz)
Data transfer speeds:	• 150Mbps (max) @ 20MHz • 300Mbps (max) @ 40MHz

WIRELESS SECURITY

VIDEO OUTPUR

Support Output Resolution:	HDMI: 1080P 24/30/60Hz, 720P24/60Hz , XGA, ,WXGA
----------------------------	---

CONNECTOR

Wireless(802.11a/b/g/n)2.4G, Network: 2T2R

Type Micro USB B (x1) (for Power:

HDMI connecton)

Switch HDMI & MHL Slide Switch: function.

POWER

DC:	5V/1A or MHL by switch
Consumption:	5W (Maximum) No standby mode

CONTROLS

Setitng:	Control by virtual
	remote on APP

OPERATING CONDITION

Temperature:	23°F to 113°F (-5°C to 45°C)
Humidity:	0% to 95% Non- Condensing
Altitude:	0 to + 13123 ft

STORAGE CONDITION

STORAGE CONDITION	
Temperature:	-22°F to 140°F (-30°C to +60°C)
Humidity:	0% to 95% Non- Condensing
Altitude:	0 to + 50033 ft
DIMENSIONS	
Physical:	94.3 x 32.34 x12.54 (mm)
WEIGHT	
Net:	0.06 (lbs)
Gross:	0.22 (lbs)
REGULATIONS	
Safety/EMC:	FCC-B, CE, ErP, RoHS
Wi-Fi:	FCC-ID, CE R&TTE
USER GUIDE	
Language (Print):	English (WW)
Language (Digital):	English, French and Spanish(VSA) English, German, Russian and Turkish(VSE) English and Traditional Chinese(VSI)

INCLUDED ACCESSORIES

The Top Level Assembly shall consist of :	
1.VC10	
2.HDMI extender	
3.UBA cable (A to micro B)	
4.QSG	