



# L-PAD 12CX

## SPECIFICATIONS

Electronic specifications

FREQUENCY RESPONSE:  
20 Hz ÷ 22000 kHz

Inputs

MIC:  
6

GAIN RANGE:  
0 dB ÷ 50 dB

MIC INPUTS IMPEDANCE:  
2 kohm

LOW CUT:  
75 Hz

PHANTOM POWER +48V:  
Yes

MONO LINE:  
4

GAIN SELECTION:  
15 dB ÷ 35 dB

LINE INPUT IMPEDANCE:  
10 kohm

Outputs

MAIN MIX:  
1

CONTROL ROOM:  
Yes

FX SEND:  
1

AUX SEND:  
1

AUX OUTPUT:  
2

PHONES:  
1

2 TRACK:  
Yes



---

**Outputs specifications****MAIN OUT IMPEDANCE:**  
120 ohm**MAIN OUT LEVEL:**  
22 dBu**AUX OUT IMPEDANCE:**  
120 ohm**AUX OUT LEVEL:**  
16 dBu

---

**Compressors****RCF COMPRESSORS:**  
On Channel 1-4

---

**EQ****INPUT CHANNELS EQ:**  
3

---

**Auxiliary sends****AUX:**  
1 PRE/POST**FX POST:**  
1

---

**Internal Effects****SEND EFFECTS:**  
99

---

**Other features****FOOTSWITCH:**  
Yes

---

**Electrical specifications****POWER SUPPLY:**  
Internal**VOLTAGE REQUIREMENTS:**  
100 V - 240 V**POWER CONSUMPTION (MAX):**  
40 W

---

**Standard compliance****CE MARKING:**  
Yes

---

**Physical specifications****CABINET/CASE MATERIAL:**  
ABS

---

**Size****HEIGHT:**  
93 mm / 3.66 inches**WIDTH:**  
341 mm / 13.43 inches**DEPTH:**  
474 mm / 18.66 inches



---

Shipping informations

PACKAGE HEIGHT:  
160 mm / 6.3 inches

PACKAGE WIDTH:  
540 mm / 21.26 inches

PACKAGE DEPTH:  
440 mm / 17.32 inches

PACKAGE WEIGHT:  
5.04 kg / 11.11 lbs

---